



PRODUCT SPECIFICATIONS

Linear Phone Booth



MADE IN THE USA

LINEAR PHONE BOOTH PRODUCT SPECIFICATIONS



STANDARD FEATURES

External dimensions: 45" w x 45" d x 89" h

Internal dimensions: 39" w x 39" d x 83" h

10.6 square feet interior space

Left hand door: 35.375" w

Weight: 840 lbs

Est. installation time: 2 people x 3 hours (multiple units can be installed at a reduced time per unit)

Aluminum Frame (12 powder coat colors)

Exterior Panels (12 laminate or 24 fabric colors)

Interior Panels (24 fabric colors)

Acoustic rear wall

Occupancy sensor

Enclosed acoustic fleece ceiling with sprinkler knock out

Adjustable air circulation fan (33-90 air changes per hour)

Adjustable LED ceiling light panel (758 lumens)

Power source: 12-ft corded 3-prong UL Listed plug

Leveling glides

Unit sits on existing floor with 1/2" threshold

AVAILABLE OPTIONS

Right hand door

3/8" glass rear wall

Seated or standing height work surface (39" x 15.5")

Cove 2 power + 2 USB (mounted in work surface)

AirCharge wireless charging unit

Seismic kit

OASIS BERCO LINEAR PHONE BOOTHS ARE "PLUG & PLAY"

An Advanced Power Strip (APS) comes installed in the corner of the ceiling of your Linear Phone Booth. ALL electrical components (occupancy sensor, fan, LED light, power/USB unit) plug directly into this unit, then the 12' cord from the APS runs from the ceiling down the inside of the side wall and out through a grommet, leaving about 6' of cord to plug into your standard 120v wall outlet.

ETL LISTED TO CONFORM TO UL STD 962

